

OVEN UNIVERSAL (ELEMENTS ON THREE SIDES) TEMP. UPTO 250°C

DESCRIPTION:

Double walled, inner made of thick stainless steel/Aluminium, outer made of heavy duty M. Steel duly powder coated. Insulation between inner and outer wall is done with 75mm thick glass wool to prevent any heat loss. Provided with double walled door with inner made of thick stainless steel and outer is made of M. Steel duly powder coated painted. Door is provided with best quality handle, gasket etc. Inner chamber is provided with 2/3 nos. Perforated stainless steel / Aluminium. Temp range is from ambient to 250°C and is controlled by thermostat and is indicated by "L" shape thermometer. Heating is done with ISI mark heating elements made from ni-chrome heating wire placed in porcelain cups in bottom as well as in sides to maintain the uniformity of the temp.

ALUMINIUM THERMOSTAT S.S. THERMOSTAT



MODEL: GEN-005

SIZE INSIDE CHAMBER: (W X D X H)

- ❖ 300 mm x 300 mm x 300 mm
- ❖ 355 mm x 355 mm x 355 mm
- ❖ 455 mm x 455 mm x 455 mm
- ❖ 455 mm x 455 mm x 605 mm
- ❖ 605 mm x 605 mm x 605 mm
- ❖ 605 mm x 455 mm x 910 mm
- ❖ 605 mm x 605 mm x 910 mm

OPTIONAL ACCESSORIES

- ❖ Air circulating fan
- ❖ Microprocessor PID Control
- ❖ Digital Temp. Controller
- ❖ Digital Timer



GenNEXT Lab Technologies Pvt. Ltd

(An ISO 9001:2015 Certified Company)

Office No. 3, CSC-5, 1st Floor, Gole Market, Sector-9, Rohini, Delhi – 110085

Email: sales@gennextlab.com & gennextlab@gmail.com

Website: www.gennextlab.com